

CITY OF VISTA BUSINESS LICENSE (1 COPY)

CALOSHA PERMIT (1 COPY)

FOLLOWING EMAIL ADDRESS:

PLEASE SEND EMAIL SUBMISSIONS TO THE

encroachmentpermit@vista.gov

ENCROACHMENT PERMIT APPLICATION FORM SEWER LATERAL CONNECTION

NOTE: 36" MINIMUM COVER FOR UTILITIES IN RIGHT-OF-WAY

ENGINEERING DEPARTMENT

200 CIVIC CENTER DR. VISTA, CA 92084 (760) 639-6111

Please print required information JOB AND OR DRAWING NUMBER: ISSUED BY: DATE: JOB SITE ADDRESS OR DESCRIPTION: PERMIT #: PERMIT EXPIRATION DATE: **48 HOUR NOTICE REQUIRED FOR** ASSESSOR'S PARCEL NUMBER (APN): INSPECTION AND PRIOR TO START OF WORK CALL (760) 639-6113 CONTRACTOR: YOU MUST CALL UNDERGROUND SERVICE ALERT AT CONTRACTOR'S MAILING ADDRESS: (1-800-422-4133) (2) WORKING DAYS PRIOR TO WORK UNDERGROUND SERVICE ALERT NO. CITY ZIP THIS PERMIT IS INVALID WITHOUT THIS NUMBER **EMAIL ADDRESS:** A CASH SECURITY is required for trench excavation or any work not covered by construction bonds. CASH SECURITY shall be a minimum PHONE#: FAX#: of \$500 or equal to the cost of the proposed improvements within the City's right-of-way. CASH SECURITY may be returned as follows. For STATE LICENSE NUMBER **BUSINESS LICENSE NUMBER** deposit amounts greater than \$500, ninety percent (90%) of the CASH SECURITY may be returned upon completion and approval of the improvements by the City Engineer or his designee. The remaining ten **DESCRIPTION OF WORK:** percent (10%) or a minimum of \$500 will be retained for a period of (1) year after the date that the work is completed. CASH SECURITY will be forfeited and used to correct defects, unacceptable work, trench failures or subsidence if corrective work is not completed within (5) working days after notification. I agree to save, keep and hold harmless the CITY OF VISTA, its JOB SITE CONTACT: officers and agents, from all damages, costs, or expenses in law or equity that may at any time arise or be set up because of damages **CELL PHONE #** to property, or of personal injury received by reason of or in the course of performing work, which may be caused by any willful or START omission by the contractor, or any of the contractor's employees, DATE or any sub-contractor. The CITY OF VISTA will not be liable for any **ESTIMATED** accident, loss or damage to the work prior to its completion and COMPLETION DATE acceptance. THE FOLLOWING MUST BE INCLUDED OR EMAILED I am aware of the provisions of Section 3700 of the Labor Code WITH PERMIT APPLICATION: which requires every employer to be insured against liability, for TRAFFIC CONTROL PLANS (1 COPY) workman's compensation or to undertake self-insurance in SITE PLAN / VICINITY MAP (1 COPY) accordance with the provisions of said Labor Code and I will **CONSTRUCTION PLANS (1 COPY)** comply with such provisions before commencing the performance of the work of this contract. LIABILITY INSURANCE (1 COPY) WORKMAN'S COMP INSURANCE (1 COPY) I hereby acknowledge that I have read this application and certify

NOTICE: THIS IS NOT AN ENCROACHMENT PERMIT - CONTRACTOR MUST SIGN ACTUAL PERMIT IN PERSON

this permit.

SIGNATURE

PRINT NAME

DATE

that the information given is correct. I agree to comply with all

applicable city ordinances, state laws and with the requirements of



CITY OF VISTA

Requirements for Encroachment Permits

- 1. Must have State Contractor's License.
- 2. Required License Types: For trenching, only A, C-34, C-36 & C42 allowed Additional License Types may be allowed for Surface Improvements
- 3. State of California Occupational Safety and Health Permit (CALOSHA).
- 4. Must submit applicable Underground Service Alert Number, if applicable.
- 5. Must have valid City of Vista Business License.
- 6. Must have Workers Compensation Insurance with the City of Vista as Certificate Holder.
- 7. Must have Liability Insurance with the City of Vista listed as the Certificate Holder and as Additional Insured.

If working in a street or easement, liability amount must be at least \$1,000,000.00 For surface improvements - sidewalks or driveways amount must be \$500,000.00

- 8. Must have \$1,000,000.00 of pollution liability insurance if doing any work on or within public sewer manholes or public sewer mains.
- 9. Must adhere to the attached City Notices for Traffic Control, Materials, and Stormwater standards.

PLEASE NOTE

Additional Insured Endorsements must be included as attachments to the Certificate of Liability Insurance

***** Endorsements must cover Ongoing and Completed Operations *****

10. Permit Fee & Required Cash Trust Deposit: Minimum cost of permit is \$1,832.33 plus a minimum cash trust deposit of \$500.00 or an amount equal to the cost of the improvements being done within the City's right-of-way. Minimum permit fee covers 3 hours of inspection time and 30 minutes for preconstruction meetings. Additional fees will be due if more than 3 hours of inspection time is required.

Trust Deposit may be returned as follows.

Ninety percent (90%) of Cash Deposit may be returned upon completion and approval of the improvements by the City Engineer or his designee.

The remaining ten percent (10%) or a minimum of \$500.00 will be held for a period of one year after the completion and final approval of the work and may be returned if the funds are not required to correct improvement defects, unacceptable surface work and trench failure or subsidence which is not corrected within (5) working days after notification.

APPROVABLE TRAFFIC CONTROL PLANS MUST TO BE SUBMITTED WITH PERMIT APPLICATION. ISSUANCE OF PERMIT MAY BE DELAYED IF NOT SUBMITTED.

TRAFFIC CONTROL PLANS MUST MEET ALL REQUIREMENTS MANDATED WITHIN THE CALIFORNIA MANUAL ON TRAFFIC CONTROL DEVICES.



CITY OF VISTA - Notice

The following General Traffic Control Conditions shall be considered a part of the City of Vista Encroachment Permit

Traffic Control and Standards

- 1. Telephone Engineering Inspection at 760-639-6113, 48 hours prior to any work in the City right-of-way.
- 2. The traffic control plan must be prepared by either a California licensed Traffic Control Services Consultant (C31 Contractor's License Construction Zone Traffic Control Contractor) or be a California registered Traffic or Civil Engineer.
- 3. The traffic control plan must be in accordance with the latest edition of the California MUTCD or the San Diego Regional Standard Drawings.
- 4. The Encroachment Permit shall be kept on the worksite during all ongoing work with the City-approved traffic control plan.
- 5. Traffic control shall be set and maintained per the City approved traffic control plan. Barricades shall be Type II Flashing, with reflectorized delineators and signs, if required for night operations. Minimum lane width is 11 feet.
- 6. No street shall be closed without the approval of the Traffic Engineer pursuant to a City approved traffic control plan.
- 7. Pedestrian walkway shall be left open or detoured using a minimum four-foot-wide safe passageway pursuant to a City approved traffic control plan.
- 8. Normal working hours are 7:00 a.m. 5:00 p.m., Monday through Friday unless indicated otherwise on the City approved traffic control plan.
- 9. Work in the public right-of-way shall be Monday through Friday only. No work is allowed on Saturday, Sunday, or City Holidays without prior City approval.
- 10. Upon permit expiration, all work ceases until a new permit application is submitted and approved. Existing permit time extension requests must be submitted prior to expiration date of permit.
- 11. No construction vehicles shall be parked upon public sidewalks. VCC 10.24.040.
- 12. It is the permittee's responsibility to protect against any dirt or debris from being deposited within the City storm drain system. See attached stormwater pollution prevention requirements.
- 13. The permittee is required to immediately comply with all directives issued by the City Inspector to eliminate dust, mud, or other site nuisance.

OF VIGINIANTED JANUARY ME

CITY OF VISTA - Notice

The following Materials and Standards shall be considered a part of the City of Vista Encroachment Permit

Materials and Standards

- 1. The permittee is responsible to perform all work and conduct operations per City approved editions of the SSPWC, SDRSD, CITY STDS, CODES, this PERMIT, and all other applicable requirements.
- 2. No trenches shall be left open overnight. Trenches shall either be plated with recessed non-skid trench plates and all edges sealed with temporary AC seal, or backfilled and paved with a minimum of 2" of compacted 3/4" B2 PG 64-10 hot mix. Temporary AC Cold Mix is not allowed unless authorized by the City Engineer. For trenches wider than 4-feet, a paving machine is required.
- 3. Curb, gutter, sidewalk, driveways, and curb ramps shall be sawcut to an even line and be removed joint to joint per SDRSD G-11.
- 4. Curb and gutter and cross gutter shall be removed as directed by the City Inspector. Concrete removal will require a 1' minimum section of asphalt sawcut and repave.
- 5. Permanent asphalt placement shall be per City of Vista Std. Dwg. SRF-08A & 08B. Two-inch (2") grind and cap is required for all trenches and shall extend a minimum of 4 feet wide or 12-inches from the outside edge of the trench whichever is greater. AC shall be placed using a spreader box or a paving machine. Cap with 1/2" Med. C2-PG 64-10 RAP unless otherwise noted. Streets paved with rubberized asphalt shall be capped with the same material.
- 6. All damaged roadway striping shall be replaced in kind.
- 7. All concrete placed shall be transit mix, unless waived by the City Inspector.
- 8. Two-sack slurry backfill is required when tunneling under curb and gutter.
- 9. All subgrade (12" depth) and basegrade material shall be compacted to 95 percent density. Sidewalk sub/base material shall be compacted to 90 percent density. Certification, including compaction testing, shall be provided by the Permitee unless waived by the City Inspector.
- 10. No excavated material shall be hauled to a site within the City of Vista, without City Inspector knowledge of the end haul location, and the appropriate permits.
- 11. Any continuous hauling operation will require a City approved Haul Route Permit, prior to commencing the haul. Hauling of dirt/rock etc. without this permit may subject this haul to an immediate Stop Work Notice.
- 12. Approved City materials for construction include:
 - a. Asphalt: Surface course ½" Med. C2-PG 64-10 RAP, Min. .10 thick

Base course - 3/4" Med. B-PG 64-10 RAP

Berm - D2-AR-8000

[Performance Grade (PG) asphalt binder may be substituted for AR-8000 asphalt binder in AC Berm]

- b. Concrete for structures 6-sack 3250 PSI min.
- c. Concrete for curb and gutters, sidewalks, driveways 520-C-2500 min.
- d. Base material for curb ramps 6" Class II/Caltrans 26-1.02B
- e. Street base material Class II
- f. Sidewalk base material 6" Class II
- g. Curing compound on all concrete Type I SSPWC 303-5.6

All standards are considered minimum and may be revised by the City depending upon field considerations, standards and materials approved on a signed City plan, supercede above materials and standards. It is the permittee's responsibility to understand and implement all Standards, Codes and other applicable requirements.

CITY OF VISTA - NOTICE

The following Stormwater Pollution Prevention Requirements shall be considered part of the City of Vista Encroachment Permit

Stormwater Pollution Prevention Requirements

Project Activity	Required Pollution Prevention
Trash & Waste Generation	Permittee shall inform any on-site employees of these pollution prevention requirements.
**REQUIRED FOR ALL	Within or adjacent to the encroachment area, permittee shall:
PROJECTS**	Collect and contain all construction trash, waste, and debris
	Promptly contain and clean any spill on site
	Routinely inspect site, remove loose trash, and prevent spills
	Properly dispose of any hazardous materials
	Not wash down surfaces unless water is collected and removed or directed to landscape
	Close lids in trash collection areas when not in use
Digging of Dirt – excavation,	Within or adjacent to the encroachment area, permittee shall:
trenching, demolition of	Prevent dirt from migrating into street, sidewalk, or storm drain
structures or grading	Protect nearby storm drain inlets with perimeter controls and/or filter fabric
	Install and maintain effective erosion and sediment controls
	Cover exposed soils using mulch, tarps, or erosion control devices
	Secure tarps over dirt and debris piles
	Routinely sweep site to remove and properly dispose of dirt generated by work
Driveway or Sidewalk	Within or adjacent to the encroachment area, permittee shall:
,	Direct surface runoff to landscape areas, where feasible
	Follow Required Pollution Prevention Requirements for "Digging of Dirt"
	 Follow Required Pollution Prevention Requirements for "Concrete, Paint, Mortar, or Stucco Work"
Concrete, Paint, Mortar, or	Within or adjacent to the encroachment area, permittee shall:
Stucco Work	Contain wet mixing areas within confined area
	 Prevent concrete, paint, mortar or stucco material from migrating into street, sidewalk or storm drain
	Properly dispose of waste material generated by work
Temporary Storage of	Within or adjacent to the encroachment area, permittee shall:
Materials Outside	Elevate work materials off ground where possible, such as on pallets
Washing of Material	Secure tarps over work materials stored outside Within or adjacent to the encroachment area, permittee shall:
Washing of Material, Equipment, or Surface	Not wash down surfaces unless water is collected and removed or directed to
	landscape
Landscaping and Irrigation	Within or adjacent to the encroachment area, permittee shall:
Systems	Not store landscape materials in street
	Prevent dirt from migrating into street, sidewalk, or storm drain
	Secure tarps over piles of mulch or soil
	Routinely sweep site to remove and properly dispose of dirt generated by work
	Not wash down surfaces unless water is collected and removed or directed to landscape
	Test irrigation system, preventing overspray and runoff from hard surfaces



CITY OF VISTA New Sewer Lateral Location Diagram

ob Address:		
Owner:		
ssessor Parcel No	Sewer Permit No	
Approximate length of lateral:		
Approximate depth of lateral:	at sewer main at property line	
Lateral Pipe Size:	Lateral Material:	
Note: Each Sewer Lateral requi	ires a clean-out and backwater valve located on private	
property as close to the propert	y line as possible. Show location below.	
Approximate location of lateral	in feet from nearest sewer manhole (sketch):	